



AAM Competition GT-R Transmission Brace **INSTALLATION INSTRUCTIONS**

WARNING FOR INSTALLER OF THIS PRODUCT

*** Product(s) are designed for off-road / competition use only ***

This AAM Competition, LLC product requires above average mechanical ability to install properly. Installation requires the appropriate tools for tightening and loosening nuts and bolts involved for the installation of this kit. As with all mechanical projects, take appropriate precautions for your personal safety and for the proper care and treatment of the vehicle being serviced. Be sure and read through all directions before attempting.

Copyright AAM Competition, LLC 2014

IF PRINTING, PLEASE DO SO IN COLOR TO BETTER SEE ILLUSTRATIONS WHICH HAVE COLOR CODED ARROWS.

Tools

- Ratchet
- 14mm Socket
- Torque Wrench

Parts List

- AAM Competition Transmission Brace (x1)

Instructions

1. Mounting area location



2. Removal of OE part(s)- Remove the top 4 differential bolts with 14mm socket/ratchet



3. Remove top two bolts on left and right transmission mount bracket



4. Fitment of new parts- Fit Transmission Brace



5. Place all 8 bolts removed back in their corresponding holes. Do not tighten until all bolts are threaded in. Torque bolts to 36 ft/lbs (49 nm)

